

The following Listing of Claims will replace all prior versions, and listings, of claims in the application.

LISTING OF CLAIMS:

1. (Currently Amended) A damper mechanism comprising:
a first rotary member, said first rotary member having a plurality of internal teeth;
a second rotary member being configured to rotate relative to said first rotary member, said second rotary members having a plurality of external teeth, said plurality of external teeth being arranged to have a rotational gap with respect to said plurality of internal teeth;
a damper section being configured to couple elastically said first rotary member and said second rotary member together in a rotational direction;
a friction mechanism being configured to generate friction when said first rotary member and said second rotary member rotate relative to each other;
a friction suppressing mechanism being configured to prevent said friction mechanism from operating within a prescribed angular range, said prescribed angular range having a positive rotational side and a negative rotational side corresponding to said first rotary member being respectively rotated relative to said second rotary member in a first rotational direction and second rotational direction opposite said first rotational direction; and
an elastic member being configured to soften the impact between members that contact each other at an end of said prescribed angular range only on one of said positive rotational side or said negative rotational side, said elastic member being disposed rotationally between said internal teeth and said external teeth.

2. (Original) The damper mechanism according to claim 1, wherein said elastic member is arranged to be compressed in the rotational direction within said prescribed angular range.

3. (Previously Presented) The damper mechanism according to claim 2, wherein

said friction mechanism has two friction rotary members aligned in the rotational direction.

4. (Cancelled).

5. (Cancelled).

6. (Cancelled).

7. (Previously Presented) The damper mechanism according to claim 1, wherein

said friction mechanism has two friction rotary members aligned in the rotational direction.

8. (Cancelled).

9. (Cancelled).

10. (Cancelled).

11. (Currently amended) A clutch disk assembly being configured to transfer torque from an engine and dampen vibrations from a flywheel, the clutch disk assembly comprising:

an input rotary member, said input rotary member having a plurality of internal teeth;

an output rotary member being disposed to rotate relative to said input rotary member, said output rotary members having a plurality of external teeth, said plurality of external teeth being arranged to have a rotational gap with respect to said plurality of internal teeth;

a damper mechanism having

a spring member being configured to couple rotationally said input rotary member and said output rotary member, and

a torsion characteristic having

a positive side corresponding to said input rotary member being twisted in a rotational drive direction with respect to said output rotary member,

a negative side corresponding to said input rotary member being twisted in a direction opposite said rotational drive direction with respect to said output rotary member,

a first stage, and

a second stage corresponding to said spring member being compressed, said second stage having a higher rigidity than said first stage, said second stage existing on both said positive side and said negative side;

a friction mechanism being configured to generate friction when said input rotary member and said output rotary member rotate relative to each other within said second stage and said spring member exerts an elastic force;

a friction suppressing mechanism being configured to secure a rotational gap in said second stage, said friction suppressing mechanism being configured to prevent said elastic force of said spring member from acting on said friction mechanism within a prescribed angular range; and

an elastic member being configured to soften the impact between members that contact each other at an end of said prescribed angular range only on one of said positive side or said negative side, said elastic member being disposed rotationally between said internal teeth and said external teeth.

12. (Original) The clutch disk assembly according to claim 11, wherein said elastic member is arranged to be compressed in the rotational direction within said prescribed angular range.

13. (Previously Presented) The clutch disk assembly according to claim 12, wherein

said friction mechanism has two friction rotary members aligned in the rotational direction.

14. (Cancelled).

15. (Cancelled).

Appl. No. 10/725,289
Amendment dated July 2, 2004
Reply to Office Action of May 19, 2004

16. (Cancelled).

17. (Previously Presented) The clutch disk assembly according to claim 11,
wherein

said friction mechanism has two friction rotary members aligned in the rotational
direction.

18. (Cancelled).

19. (Cancelled).

20. (Cancelled).